

PRECONTRAIN[®]

832

WIDTH: 180 cm / 270 cm (white)	WEIGHT: 850 g/sqm
JUMBO ROLLS*: ± 300 lm	LENGTHS*: ± 50 lm (30 lm white)



FLEXIBLE DOORS



INDUSTRIAL BUILDINGS



GUARANTEES AND LABELS



ADVANTAGES

- FERRARI[®] PRÉCONTRAIN[®] TECHNOLOGY:
 - EXCEPTIONAL DIMENSIONAL STABILITY
 - HIGH DURABILITY
 - EXCELLENT WELDABILITY
- 10 COLOURS AVAILABLE
- FIRE RETARDANT PANAMA QUALITY BASE CLOTH: VERY GOOD MECHANICAL STRENGTH

COLOURS & REFERENCES

(COLOURS ARE INDICATIVE)

	Ref. 832-8100 (270 cm width)
	Ref. 832-8102 (180 cm width)
	Ref. 832-1071 RAL 7038
	Ref. 832-1076 RAL 1015
	Ref. 832-1061 RAL 1003
	Ref. 832-1065 RAL 3002
	Ref. 832-1051 RAL 5002
	Ref. 832-1053 RAL 5015
	Ref. 832-1055 RAL 6026
	Ref. 832-1075 RAL 9005
	Ref. 832-1267 (Alu)

TECHNICAL SPECIFICATIONS

	PRÉCONTRAIN [®] 832	STANDARDS
YARN	2 x 1100 dtex PES HT	TERSUISSE
WEIGHT	850 g/sqm	EN ISO 2286-2
WIDTH	180 cm (white 180 and 270 cm)	
TENSILE STRENGTH (WARP/WEFT)	400/400 daN/5 cm	EN ISO 1421
TEAR STRENGTH (WARP/WEFT)	50/50 daN	DIN 53.363
ADHESION	11/11 daN/5 cm	EN ISO 2411
FINISH	VARNISH BOTH SIDES	
FLAME RETARDANCY	M2/NFP 92-507 • Test 2/NFPA 701 • CSFM T19 • B1/DIN 4102-1 • BS 7837 • B1/ONORM B 3800-1 • M2/UNE 23.727 • VKF 5.2/SN 198898 • SITAC/SINTEF/ETA/SIS 650082 • ROCT 30444.97	
HANDLING TEMPERATURE RANGE	-30°C/+70°C	
QUALITY MANAGEMENT SYSTEM		ISO 9001

The technical characteristics shown are average values given as a guide and may be modified.
*Our packaging data are given for information only and may vary as a function of manufacturing conditions.